

MALAYSIA GEOSPATIAL FORUM

SABAH INTERNATIONAL SURVEYORS CONGRESS 2014

11 -12 MARCH 2014

KOTA KINABALU, SABAH, MALAYSIA

**FOSTERING QUANTITY SURVEYORS IN
CIVIL ENGINEERING WORKS**

**Sr. Jailani Jasmani MRISM, ICECA
Deputy Chair, Quantity Surveying Division,
Royal Institution of Surveyors Malaysia**

Director, JUB Central Sdn Bhd




WHAT IS CIVIL ENGINEERING WORKS.~



CIVIL ENGINEERING WORKS :

- **planning, design, construction, maintenance and management of physical infrastructure networks.**
- **Fixed structures, public works related to earth, water or energy and their processes.**
- **power plants, bridges, roads, railways, structures, water supply, irrigation, the natural environment, sewer, flood control, transportation and traffic.**



CHALLENGES:


- ▶ Knowledge in civil engineering
- ▶ Terminologies
- ▶ Special requirements
- ▶ Alternative designs & alternative materials
- ▶ Value engineering exercises
- ▶ Latest technology
- ▶ Identify major costs:
 - ▶ Controllable
 - ▶ uncontrollable
- ▶ Unit costs and all-in cost
- ▶ Elemental cost analysis



HIGHWAYS



HIGHWAYS



- ▶ A public road is a major road connecting two or more destinations.
- ▶ Often named and numbered eg E2 (PLUS)

NORMAL HIGHWAY



ELEVATED HIGHWAY



SINGLE CARRIAGEWAY

one, two or more lanes arranged within a single carriageway with no median (divider) to separate opposing flows of traffic.



2 lanes



3 lanes



4 lanes

DUAL CARRIAGEWAY

For traffic travelling in opposite directions separated by a central reservation. Roads with two or more carriageways which are designed to higher standards with controlled access.


- 1 lane in each direction.
- 2 lanes in each direction.
- 3 lanes in each direction.
- 4 lanes in each direction.



ROAD INTERCHANGES


- A road junction that uses grade separation, and one or more ramps, to permit traffic to pass through the junction without crossing any other traffic stream.
- Interchanges are used when at least one of the roads is a limited-access divided highway (eg expressway or freeway)

TYPES OF INTERCHANGES




Cloverleaf Interchange

TYPES OF INTERCHANGES




Diamond Interchange

TYPES OF INTERCHANGES



Stack Interchange

TYPES OF INTERCHANGES



Trumpet Interchange

CHALLENGES IN HIGHWAY PROJECTS

- ▶ Working on a “life” highway
- ▶ Extra costs on :-
 - ▶ Preliminary works
 - ▶ Temporary works
 - ▶ Relocation of existing services
 - ▶ Temporary road diversion
 - ▶ Overtime works / odd hours
 - ▶ Risks to road users - extra safety measures



BRIDGE




BRIDGE

- ▶ An overpass that allows one transportation route, such as a highway or railroad line, to cross over another without traffic interference between the two routes
- ▶ To cross over river, straits, lake, deep valley, ravine, land




TYPES OF BRIDGE

1. Beam Bridge
 - ▶ Girder Bridge
 - ▶ Truss Bridge
 - ▶ Rigid Frame Bridge
2. Arch Bridge
3. Cantilevered Bridge
4. Suspension Bridge
5. Cable-Stayed Bridge



COMPONENTS OF A BRIDGE

- Pier & Foundation
- Abutment
- Tower
- Cable
- Anchor
- Hanger
- Deck
- Bearing
- Parapet wall




Pier Designs



Towers



Cable & Anchorage




Aluminium

Steel


Concrete

Parapet Walls


Main Components and Load Distribution of a Bridge




Concrete arch



Cantilever




Suspension




Cable-stayed

Beam Bridge


Girder Bridge




Rigid Frame Bridge



Truss Bridge






Girder Bridge





Steel Truss Bridge




Rigid Frame Bridge



Arch Bridge




through arch bridge



half-through arch bridge



deck arch bridge



portal bridge

Arch Bridge


Seri Setia, Putrajaya.




Pulau Bunting, Kedah



Cantilevered Bridge




Double-cantilevered Box Girder Bridge



SG. SANTUBONG
BRIDGE KUCHING,
SARAWAK

Suspension Bridge




Putrajaya Monorail Suspension Bridge




Cable-Stayed Bridge

fan cable stays




www.visualdictionaryonline.com

harp cable stays



Cable-Stayed Bridge (cont'd)




**Seri Wawasan Bridge,
Putrajaya.**



**Sultan Abdul Halim Mu'adzam Shah
Bridge (Second Penang Bridge)**



AIRPORTS



AIRPORT CLASSIFICATIONS

- ▶ Based on “highest requirement” of an aircraft that can use the airport.
- ▶ In layman terms, the “biggest” aircraft that can land at the airport.


AERODROME CODE REFERENCE

Table I-1. Aerodrome reference code
(see 1.3.2 to 1.3.4)

Code element 1		Code element 2		
Code number (1)	Aeroplane reference field length (2)	Code letter (3)	Wing span (4)	Outer main gear wheel span ^a (5)
1	Less than 800 m	A	Up to but not including 15 m	Up to but not including 4.5 m
2	800 m up to but not including 1 200 m	B	15 m up to but not including 24 m	4.5 m up to but not including 6 m
3	1 200 m up to but not including 1 800 m	C	24 m up to but not including 36 m	6 m up to but not including 9 m
4	1 800 m and over	D	36 m up to but not including 52 m	9 m up to but not including 14 m
		E	52 m up to but not including 65 m	9 m up to but not including 14 m
		F	65m up to but not including 80m	14m up to but not including 16m

a. Distance between the outside edges of the main gear wheels.

AIRPORT COMPONENTS



Main components :-

▶ LANDSIDE

▶ Main Terminal Building (MTB)

- ▶ to serve passengers and facilities

▶ Airport Traffic Control Tower (ATC)

- ▶ Air controllers responsible for the separation and efficient movement of aircraft and vehicles.

▶ Meteorological Department

- ▶ meteorological service for aircraft flying in and out

Main components (cont'd):-


- ▶ **AIRSIDE** - where aircrafts operate
 - ▶ **Runway**
 - ▶ Aircraft take off and land.
 - ▶ **Apron**
 - ▶ Passengers embark and debark and where aircraft are parked
 - ▶ **Taxiway**
 - ▶ Movement between runway & terminal
 - ▶ **Hangar (MRO)**
 - ▶ To hold aircraft in a protective storage

AIRPORT TERMINOLOGIES

- ▶ DCA - Department of Civil Aviation
- ▶ Airside - Airfield
- ▶ Landside - Surface transportation
- ▶ MTB - Main Terminal Building
- ▶ ATC - Air Traffic Control
- ▶ MRO - Maintenance, Repair & Overhaul (hangar)
- ▶ ILS - Instrument Landing System
- ▶ FIDS - Flight Information Display System
- ▶ BHS - Baggage Handling System

WATER TREATMENT PLANT


INTAKE



WATER CYCLE



Water Treatment Process Flow



Pengagihan Air




Pengagihan Bekalan Air



Water Treatment Process

- ▶ **Filtration** : Process of removing suspended solids from water by passing the water through a permeable fabric or porous bed of materials.
- ▶ **Chlorination** : Adding disinfectants to destroy microorganisms that can cause disease in human. Adding of lime to reduce acidity of water.

Water Treatment Process



Water Treatment Process (Cont'd)

River

Raw water flows to the raw water pump sump.

Raw water pumps

water is pumped to treatment plant via a raw water pipe.

Aerator

Create turbulence to achieve dissolved oxygen content of 80% saturation. Pre-lime & primary coagulant, poly aluminium chloride (PACI) are added.

Filters

Rapid gravity sand filters - remove fine particles that have not settled in the clarification process. Clarified water is filtered through a sand filter media to trap unsettled particles.

Clarifiers

Clarifiers - floc concentration, collection & discharge. Settled water overflows into collection channels for onward flow to the filters.


Mixing chamber

Flash mixing chamber where a flocculent aid (polyelectrolyte) is added to enhance floc formation for easier removal in the clarification process.

Cont'd



Water Treatment Process (Cont'd)



Components of Water Treatment Cycle

- ▶ **Dams** - A barrier that impounds water or underground streams. Collect raw water from rivers.
- ▶ **Raw water pipes** - Transfer raw water from dams to reservoir.
- ▶ **Water treatment plants** - Treat raw water to become potable water.
- ▶ **Treated water pipes** - Transfer treated water to reservoir
- ▶ **Elevated water tank** - Restore water

COSTS ANALYSIS OF WATER TREATMENT WORKS

MILD STEEL CONCRETE LINING PIPE

Size of Pipe	Estimated Rate
	(RM)
500 mm dia. MSCL	490.00/m
700 mm dia. MSCL	620.00/m
800 mm dia. MSCL	690.00/m
1000 mm dia. MSCL	910.00/m
1200 mm dia. MSCL	1,180.00/m

ELEVATED RESERVOIR

- Rate (RM)/litre = RM 1.00/litre

RESERVOIR

- Rate (RM)/litre = RM 0.50/litre

COSTS ANALYSIS OF WATER TREATMENT WORKS

HOT TAPPING WORKS

Size of Pipe	Estimated Rate
	(RM)
250mm dia. MSCL	6,000.00 /no
300-450mm dia. MSCL	21,000.00/no
400-500mm dia. MSCL	25,000.00/no
700-900mm dia. MSCL	50,000.00/no
800mm dia. MSCL	80,000.00/no
900mm dia. MSCL	100,000.00/no


LINE-STOPPING WORK

Size of Pipe	Estimated Rate/LS
	(RM)
700 dia. mm	500,000.00
900 dia. mm	600,000.00
1200 dia. mm	1,000,000.00

WASTE WATER MANAGEMENT



Wastewater Treatment Flow Chart



Wastewater Treatment Technologies

- ▶ Conventional Activated Sludge System (CASS)
- ▶ Advance Oxidation Process
- ▶ Aerated Lagoon
- ▶ Anaerobic Digester
- ▶ Sequential Batch Reactor (SBR)
- ▶ Anaerobic, Anoxic and Oxidic Zone (A2O)
- ▶ Multi Step Feed Aeration




Comparison of various types of STP in Malaysia

Sewage Treatment Plant	Treatment Process	PE	Process Plant Footprint	sqm/PE
Existing Pantai 2 STP	Aerated Lagoon	566K	136,600 m ²	0.24
Jelutong STP, Penang	Sequential Batch Reactor (SBR)	1.2mil	32,000 m ²	0.03
New Pantai 2 STP	A2O	1.43 mil	25,000 m ²	0.02
Langat CSTP - Concept Design Stage	Multi Step Feed Deep Aeration	995K		

A2O - Anaerobic, Anoxic and Oxidic Zone

- ▶ A compact treatment facility using **Advanced A2O process + sludge treatment + dewatering facilities.**
- ▶ to replace the existing aerated lagoons, which will incorporate anaerobic digestion with solid dewatering.

PANTAI 2 SEWAGE TREATMENT PLANT



A2O - Anaerobic, Anoxic and Oxic Zone & Multi Step Feed Deep Aeration

- ✓ Limited STP site space
- ✓ High level of ammonia

Deep Aeration Method


+

Step-feed multi-stage denitrification process

Step-feed multi-stage denitrification process

Influent

Deep
Aeration
Method



Anoxic Tank



Aerobic Tank

Anoxic Tank

Aerobic Tank / Oxic Tank

Under ground


Deep Aeration Method



Features of Deep Aeration Method

1. **Sizable STP in Small Footprint** : The required land is half of the one for the standard aeration method, so this can be a solution for land constraint.
2. **High Treatment Efficiency** : Baffle Plate makes/rectifies circular flow in the aeration tank.

The Status of Flow in Model Deep Aeration Tank



TERMINOLOGIES

❖ CENTRALIZED SEWAGE TREATMENT PLANT (CSTP)

- ✓ **Anti-Floatation Pile**
- ✓ **Ground Anchor**
- ✓ **Soil Nailing**
- ✓ **Primary & Secondary Clarifier**
- ✓ **Biological Nutrient Removal Reactor**
- ✓ **Anaerobic Digester**
- ✓ **Thickened Sludge Storage**
- ✓ **Effluent Chamber**

❖ SEWERS

- ✓ a) Force Main
- ✓ b) Gravity Sewers
 - **Open cut**
 - **Pipe Jacking**
 - **Micro tunneling**
 - **Pipe Bursting**
- ✓ C) Receiving Chamber
- ✓ d) Manholes and Chambers

❖ NETWORK PUMPING STATION

- ✓ **Population Equivalent (PE)**
- ✓ **Temporary Treatment Plant (TTP)**

COST ANALYSIS OF WASTEWATER TREATMENT WORKS



PIPE LAYING WORKS

FORCE MAIN

DESCRIPTION	RATE (RM)/m
100mm DI Pipe	860.00
200mm DI Pipe	1,300.00
300mm DI Pipe	1,500.00
600mm DI Pipe	1,900.00
700mm DI Pipe	2,200.00
1400mm DI Pipe	4,200.00

* method : open cut & pipe jacking for crossing

GRAVITY SEWERS

➤ Pipe jacking

DESCRIPTION	ESTIMATED RATE (RM)/m
225mm VCJP	1,600.00
300mm VCJP	1,900.00
450mm RCJP	2,400.00
600mm RCJP	3,000.00
750mm RCJP	3,500.00
900mm RCJP	4,000.00
1050mm RCJP	4,600.00
1200mm RCJP	5,500.00
1500mm RCJP	6,500.00
1800mm RCJP	7,700.00

➤ Jacking & Receiving pit

DESCRIPTION	ESTIMATED RATE (RM)/m
Jacking pits	50,000 - 185,000.00/no
Receiving pits	40,000 - 165,000.00 /no

* Rate depends on depth of pit.

B) NETWORK PUMPING STATION

DESCRIPTION	ESTIMATED RATE(RM)
NPS 1 (55,000PE)	140.00 / PE
NPS 4 (85,000PE)	100.00 / PE
NPS 5 (13,000PE)	400.00 / PE
NPS 9 (900,000PE)	40.00 / PE
NPS 10 (12,000PE)	420.00 / PE
NPS 12 (9,000PE)	330.00 / PE


CHALLENGES IN WASTEWATER MANAGEMENT

Rapid development in urban areas has increased

- ▶ importance of sustainable wastewater management
- ▶ complexity of its implementation

Complex due to:

- ▶ increased population but limited land availability
- ▶ work within developed community
- ▶ work within developed infrastructure
- ▶ Working in life STP(Sewage Treatment Plant)
- ▶ Upgrading a life STP



CHALLENGES IN WASTEWATER MANAGEMENT

Sustainable wastewater management has to address:

- ▶ Wastewater collection infrastructure issues
- ▶ Wastewater treatment issues
- ▶ Bio-solids reuse and disposal issues
- ▶ Effluent reuse issues
- ▶ Effluent dispersal issues
- ▶ Impact to environment
- ▶ Impact to social well-being of community



CASE STUDY



UPGRADING BATU BERENDAM INTERNATIONAL AIRPORT



- **Client** : Uni Integrated Sdn Bhd
- **Total contract value** : RM180 Mil.
- **Completion date** : March 2010

PROPOSED BERTAM DAF PHASE 2 WATER TREATMENT PLANT, DURIAN TUNGGAL, MELAKA

PACKAGE 1 - CONSTRUCTION AND COMPLETION OF INTAKE TOWER AND RAW WATER PUMPING STATION AT DURIAN TUNGGAL DAM AND 1200MM DIAMETER RAW WATER PIPELINE FROM DURIAN TUNGGAL DAM TO BERTAM DAF PHASE 2 WATER TREATMENT PLANT.


PACKAGE 2 - CONSTRUCTION AND COMPLETION OF 120MLD BERTAM DAF PHASE 2 WATER TREATMENT PLANT.

PACKAGE 3 - CONSTRUCTION AND COMPLETION OF 2 x 5ML NEW BERTAM BALANCING RESERVOIR, 10ML NEW SUNGAI UDANG RESERVOIR, 20ML NEW AIR SALAK RESERVOIR AND INTERCONNECTION AT EXISTING CHENG RESERVOIR AND PIPELAYING OF 1000MM, 800MM, 600MM AND 500MM MSCL PIPE

PACKAGE 4 - CONSTRUCTION AND COMPLETION OF 23ML NEW BUKIT JELUTONG RESERVOIR, INTERCONNECTION AT EXISTING BUKIT BERANGAN AND EXISTING BUKIT BERUANG RESERVOIR AND PIPELAYING OF 700MM AND 400MM MSCL PIPE



PACKAGE 2 - CONSTRUCTION AND COMPLETION OF 120MLD BERTAM DAF PHASE 2 WATER TREATMENT PLANT.



Client : Pengurusan Aset Air Berhad (PAAB)

Total contract value : RM 65,000,000.00

Date of Commencement : May 2011

Date of Completion : April 2014

PACKAGE 3 - CONSTRUCTION AND COMPLETION OF 2 x 5ML NEW BERTAM BALANCING RESERVOIR, 10ML NEW SUNGAI UDANG RESERVOIR, 20ML NEW AIR SALAK RESERVOIR AND INTERCONNECTION AT EXISTING CHENG RESERVOIR AND PIPELAYING OF 1000MM, 800MM, 600MM AND 500MM MSCL PIPE




Client : Pengurusan Aset Air Berhad (PAAB)

Date of Commencement : November 2011

Date of Completion : September 2013

Project Amount : RM 59,000,000.00

PACKAGE 4 - CONSTRUCTION AND COMPLETION OF 23ML NEW BUKIT JELUTONG RESERVOIR, INTERCONNECTION AT EXISTING BUKIT BERANGAN AND EXISTING BUKIT BERUANG RESERVOIR AND PIPELAYING OF 700MM AND 400MM MSCL PIPE



Client : Pengurusan Aset Air Berhad (PAAB)

Date of Commencement : October 2011

Date of Completion : October 2013

Project Amount : RM 29,981,722.00

Pakej D47 – Pembinaan Rangkaian Paip Pembetungan di Kawasan Petaling Jaya(Utara)



- ▶ **Client** : Jabatan Perkhidmatan Pembetungan, KeTTHA
- ▶ Upon completion capable to carry 200,000 PE of wastewater
- ▶ **Contract value** : RM 277 Mil.
- ▶ **Start date** : March 2013
- ▶ **Expected completion date** : March 2017

JELUTONG SEWAGE TREATMENT PLANT (JSTP)



- ▶ **PMC** : Kumpulan Ikhtisas Projek (M) Sdn Bhd
- ▶ **Client** : Jabatan Perkhidmatan Pembetulan, KeTTHA
- ▶ **Capacity** : to treat 1.2 Mil. PE of wastewater
- ▶ **Contract value** : RM478 Mil.
- ▶ **Completed** 2004



PANTAI 2 SEWAGE TREATMENT PLANT





Client : Jabatan Perkhidmatan Pembetungan, KeTTHA

Upon completion capable to treat 1,423,000 PE of wastewater

Total contract value : RM 983 Mil.

Start date : July 2011


Expected completion date : July 2017



A – PPR Sri Pantai
 B – Taman Permainan Kanak-kanak
 C – Pusat Komuniti
 D – Kampung Dato Tahah
 E – Gelanggang Futsal Tertutup
 F – Gelanggang Bola Keranjang

G – PPR Cempaka
 H – Padang Bolasepak
 I – Gelanggang Tennis
 J – Bangunan Pentadbiran
 K – Tangki Pencernaan Enapencemar

- Kolam pengudaraan sedia ada akan dinaiktaraf kepada loji rawatan kumbahan bersistem mekanikal bagi meningkatkan keupayaan rawatan sedia ada.
- Sebuah loji rawatan kumbahan yang mengaplikasikan sistem 'Advanced A2O' yang dapat memproses air kumbahan dan enapencemar akan dibina.



CHALLENGES:

- ▶ Knowledge in civil engineering
- ▶ Terminologies
- ▶ Special requirements
- ▶ Alternative designs & alternative materials
- ▶ Value engineering exercises
- ▶ Latest technology
- ▶ Identify major costs:
 - ▶ Controllable
 - ▶ uncontrollable
- ▶ Unit costs and all-in cost
- ▶ Elemental cost analysis



THANK YOU



dreamstime.com

